

# KNÜRR ELICON® VC / VC-E

37 to 46



## MODULAR WORKSTATION SYSTEM

Whether for video surveillance, security dispatching or engineering workstations – our comprehensive product range offers optimal **solutions for a customized, ergonomic and efficient workstation.**

The **modular design** enables a wide variety of configurations and guarantees the highest degrees of flexibility. Combinations of tables can be retrofitted or modified at any time and without considerable effort.

**High quality materials** with extruded aluminum profiles in combination with die-cast aluminum stabilizers ensure a **maximum degree of stability and sturdiness.**

**Ergonomic details** simplify daily work in various situations and environments.

A **comprehensive range of accessories** completes the Knürr Elicon workstation system: flat screen holders, PC and 19-inch rack containers, workstation lighting, usable storage trays, cable routing ducts and other extras.

## Knürr Elicon®VC-E

Electrical height adjustable Sit-Stand Workstation

### Intelligent cable routing

Covered vertical cable routing in the side section, accessible from the inside and outside

### High quality tabletops

with depths of 800 mm and 900 mm, linear or curved variants



### Modular console system

Frame widths from 1200 mm to 2000 mm

### In compliance with standards

Certified usability and ergonomics based on DIN 33419 / EN ISO 15537 and DIN EN 527-1.

### Maximum stability

Extruded aluminum profiles with die-cast aluminum stabilizers to ensure the highest degree of stability

CON20111

**Standard colors:**



**A** RAL7035  
Light gray




**B** Nelson Oak  
wood grain

**Modern design and color scheme**

Base frame in RAL 9006 white aluminium, tabletop either in RAL 7035 light gray or Nelson Oak wood grain

**Simple screen integration**

High degree of flexibility thanks to adjustable jointed screen arms



**Comfortable height adjustment**

Electric height adjustment from 650 to 1250 mm

**Flat packaging**

for reduced transport volume

**Generous cable troughs**

to accommodate socket strips, KVM switches, cables and so forth


**Sturdy rear panel**

to ensure optimal lateral stability and function as a privacy screen

CON20112

## Knürr Elicon®VC

Height adjustable (VC), in combination with electric height adjustment (VC-E)



**Knürr Elicon VC-E Module**  
(Linear)

**Knürr Elicon VC Module**  
(Linear and 90° corner)

**Simple chain-linking**  
of electrically adjustable (VC-E) and height selectable (VC) consoles

CON2013

### Standard colors:



**A** RAL7035  
Light gray



**B** Nelson Oak  
wood grain



**Height adjustable**  
in 20 mm increments from  
640 to 760 mm

**Future-proof modular design**

Expand your existing table combinations, modify your current installation or supplement it with new accessories. The modular design and multi-functional T-grooves give you all the options for future upgrades.

**Easy assembly**

Quick and easy to assemble on site



**Intelligent cable routing**

Covered vertical cable routing in the side section, accessible from the inside and outside

**Optional rear panels**

for VC consoles guarantee a uniform design

**Roomy cable troughs**

Full accessibility, including optional privacy protection using front covers and plug-in rear panel

**High quality energy chain**

for safe and convenient routing from the VC-E side section to the cable trough

CON20114

## Knürr Elicon® VC-E Side Sections Electric height adjustment

- Height adjustment range: 650 mm to 1250 mm
- Only usable in combination with Elicon VC-E Working Surfaces
- **Material / Finish**
  - Extruded aluminum profiles with die-cast aluminum stabilizers and top section
  - Steel panel covers, powder-coated
- **Color**
  - RAL9006 White aluminium
- **Supply schedule**
  - Left-hand and right-hand variants: 1 side section with lifting column, lifting column and cable duct covers
  - Center variant: 1 side section with 2 lifting columns, lifting column and cable duct covers
- **How supplied**
  - Completely preassembled

H	D	Model	Order-No	UP
590	800	Side section, left	04.265.130.7	1 unit
590	800	Side section, right	04.265.131.7	1 unit
590	800	Side section, center	04.265.132.7	1 unit



Side section, left

CON20115

Side section, right

CON20116




Side section, center

CON20117

## Maximum stability guaranteed!

Custom linking options between **VC-E** and **VC** modules




## Knürr Elicon® VC-E Working Surfaces Curved

- Single table
- Height adjustment range: 650 mm to 1250 mm
- Only usable in combination with Elicon VC-E Side Sections
- **Loading capacity**
  - 1200 N (static surface load)
- **Material / Finish**
  - Tabletop: Three-layer particle board FP/Y E1 variant, fire protection class B2
  - Tabletop cover: High pressure plastic laminate (HPL)
  - Edging: ABS
  - Stabilizer, cable trough and rear panel Steel panel, powder-coated
- **Color combination**
  - Tabletop:
    - .A RAL7035 Light gray or
    - .B Nelson Oak wood grain
  - Edging: Black gray
  - Sheet metal parts: RAL9006 White aluminium
- **Supply schedule**
  - 1 working surface with horizontal cable duct
  - 1 control unit for electrical height adjustment
  - 1 energy chain
  - 1 rear panel, bottom
- **How supplied**
  - Preassembled, flat packaging

W	D	Model	Order-no.	UP
1400	800	Curved	<b>04.265.023.x</b>	1 unit
1600	800	Curved	<b>04.265.024.x</b>	1 unit
1800	800	Curved	<b>04.265.025.x</b>	1 unit
2000	800	Curved	<b>04.265.026.x</b>	1 unit
2200	800	Curved	<b>04.265.027.x</b>	1 unit
1400	900	Curved	<b>04.265.033.x</b>	1 unit
1600	900	Curved	<b>04.265.034.x</b>	1 unit
1800	900	Curved	<b>04.265.035.x</b>	1 unit
2000	900	Curved	<b>04.265.036.x</b>	1 unit
2200	900	Curved	<b>04.265.037.x</b>	1 unit



CON20118



CON20119


## Knürr Elicon® VC-E Working Surfaces Linear

- Single table or linked
- Height adjustment range: 650 mm to 1250 mm
- Only usable in combination with Elicon VC-E Side Sections
- **Loading capacity**
  - 1200 N (static surface load)
- **Material / Finish**
  - Tabletop: Three-layer particle board FP/Y E1 variant, fire protection class B2
  - Tabletop cover: High pressure plastic laminate (HPL)
  - Edging: ABS
  - Stabilizer, cable trough and rearpanel Steel panel, powder-coated
- **Color combination**
  - Tabletop:
    - .A RAL7035 Light gray or
    - .B Nelson Oak wood grain
  - Edging: Black gray
  - Sheet metal parts: RAL9006 White aluminium
- **Supply schedule**
  - 1 working surface with horizontal cable duct
  - 1 control unit for electrical height adjustment
  - 1 energy chain
  - 1 rear panel, bottom
- **How supplied**
  - Preassembled, flat packaging

W	D	w	Model	Order-no.	UP
1200	800	1142	Linear	<b>04.265.003.x</b>	1 unit
1400	800	1342	Linear	<b>04.265.004.x</b>	1 unit
1600	800	1542	Linear	<b>04.265.005.x</b>	1 unit
1800	800	1742	Linear	<b>04.265.006.x</b>	1 unit
2000	800	1942	Linear	<b>04.265.007.x</b>	1 unit
1200	900	1142	Linear	<b>04.265.013.x</b>	1 unit
1400	900	1342	Linear	<b>04.265.014.x</b>	1 unit
1600	900	1542	Linear	<b>04.265.015.x</b>	1 unit
1800	900	1742	Linear	<b>04.265.016.x</b>	1 unit
2000	900	1942	Linear	<b>04.265.017.x</b>	1 unit



CON20120



CON20121

**Dimensions in mm:** W = Width  
 H = Height  
 D = Depth  
 h = Installation height  
 d = Useful depth  
 L = Length

HU = Standard height unit, 1 HU = 44,45 mm  
 19" = 482,6 mm, (ideal for 19" components in acc. with DIN 41494)  
 UP = Unit of packaging  
 kg = Weight

**Conversion:** 1 inch = 25,4 mm  
 1 pound = 453,6 g

Replace „x“ with the number of your color choice

## Knürr Elicon® VC Side Section Height-selectable

- Height-selectable in 20 mm increments from 640 to 760 mm
- Only usable in combination with Elicon VC Working Surfaces
- **Material / Finish**
  - Extruded aluminum profiles with die-cast aluminum stabilizers and top section
  - Steel panel covers, powder-coated
- **Color**
  - RAL9006 White aluminium
- **Supply schedule**
  - 1 side section with cable duct covers
- **How supplied**
  - Completely preassembled

W	D	Model	Order-no.	UP
500	800	Side section	04.265.120.7	1 unit



CON20123

## Knürr Elicon® VC Working Surfaces Linear


- Single table or linked
- Height-selectable in 20 mm increments from 640 to 760 mm
- Only usable in combination with Elicon VC Side Sections
- **Loading capacity**
  - 1200 N (static surface load)
- **Material / Finish**
  - Tabletop: Three-layer particle board FP/Y E1 variant, fire protection class B2
  - Tabletop cover: High pressure plastic laminate (HPL)
  - Edging: ABS
  - Stabilizer, cable trough and rear panel Steel panel, powder-coated
- **Color combination**
  - Tabletop:
    - .A RAL7035 Light gray or
    - .B Nelson Oak wood grain
  - Edging: Black gray
  - Sheet metal parts: RAL9006 White aluminium
- **Supply schedule**
  - 1 working surface with horizontal cable duct
- **How supplied**
  - Preassembled, flat packaging

W	D	MODEL	Order-no.	UP
1200	800	Linear	04.265.103.x	1 unit
1400	800	Linear	04.265.104.x	1 unit
1600	800	Linear	04.265.105.x	1 unit
1800	800	Linear	04.265.106.x	1 unit
2000	800	Linear	04.265.107.x	1 unit

1200	900	Linear	04.265.113.x	1 unit
1400	900	Linear	04.265.114.x	1 unit
1600	900	Linear	04.265.115.x	1 unit
1800	900	Linear	04.265.116.x	1 unit
2000	900	Linear	04.265.117.x	1 unit



CON20120



Please order the rear panel for foot areas separately for Elicon VC Working Surfaces!

**Dimensions in mm:** W = Width  
H = Height  
D = Depth  
h = Installation height  
d = Useful depth  
L = Length  
HU = Standard height unit, 1 HU = 44,45 mm  
19" = 482,6 mm, (ideal for 19" components in acc. with DIN 41494)  
UP = Unit of packaging  
kg = Weight



**Conversion:** 1 inch = 25,4 mm  
1 pound = 453,6 g  
Replace „x“ with the number of your color choice



## Knürr Elicon® VC Working Surfaces Corners

- Height-selectable in 20 mm increments from 640 to 760 mm
- Only usable in combination with Elicon VC Side Sections
- **Loading capacity**
  - 1200 N (static surface load)
- **Material / Finish**
  - Tabletop: Three-layer particle board FP/Y E1 variant, fire protection class B2
  - Tabletop cover: High pressure plastic laminate (HPL)
  - Edging: ABS
  - Stabilizer, cable trough and rear panel Steel panel, powder-coated
- **Color combination**
  - Tabletop:
    - .A RAL7035 Light gray or
    - .B Nelson Oak wood grain
  - Edging: Black gray
  - Sheet metal parts: RAL9006 White aluminium
- **Supply schedule**
  - 1 working surface with horizontal cable duct
- **How supplied**
  - Preassembled, flat packaging

D	Model	Order-no.	UP
800	90° corner	04.265.140.x	1 unit
800	90° wall corner	04.265.141.x	1 unit
900	90° corner	04.265.142.x	1 unit
900	90° wall corner	04.265.143.x	1 unit
800	45° corner	04.265.144.x	1 unit
900	45° corner	04.265.145.x	1 unit



## Knürr Elicon® VC Rear Panels Leg area

- **Material / Finish**
  - Steel panel, powder-coated
- **Color**
  - RAL9006 White aluminium
- **Supply schedule**
  - 1 rear panel with mounting material
- **How supplied**
  - Flat-packed kit

W	H	Model	Order-no.	UP
1200	300	Straight	04.265.153.7	1 unit
1400	300	Straight	04.265.154.7	1 unit
1600	300	Straight	04.265.155.7	1 unit
1800	300	Straight	04.265.156.7	1 unit
2000	300	Straight	04.265.157.7	1 unit
	300	90° corner	04.265.160.7	1 unit
	300	45° corner	04.265.159.7	1 unit



## Technical Container

- Technical container for rear mounting on the Elicon VC/E system table.
- With removable perforated sheet metal cladding and cable entry options on both sides.
- Cables can be guided from the raised floor into the container and via cable chains towards the working level.
- **Usable dimensions**
  - Clear depth: 200 mm
  - Clear height: 550 mm
- **Material / Finish**
  - Body: Three-layer particle board
  - Sheet metal parts: RAL9006 White aluminium


W	Order-no.	UP
1200	04.265.243.7	1 unit
1400	04.265.244.7	1 unit
1600	04.265.245.7	1 unit.
1800	04.265.246.7	1 unit
2000	04.265.247.7	1 unit



## Knürr Elicon® VC/VC-E Cover Set for cable duct

- **Material / Finish**
  - Steel panel, powder-coated
- **Color**
  - RAL9006 White aluminium
- **Supply schedule**
  - 1 rear panel
  - 1 set of covers, front side
  - Mounting material

W	H	Model	Order-no.	UP
1200	200	Straight	04.265.163.7	1 unit
1400	200	Straight	04.265.164.7	1 unit
1600	200	Straight	04.265.165.7	1 unit
1800	200	Straight	04.265.166.7	1 unit
2000	200	Straight	04.265.167.7	1 unit
	200	90° corner	04.265.170.7	1 unit
	200	45° corner	04.265.174.7	1 unit



Sectional drawing of cable trough

CON20128

## Knürr Elicon® Computer Mount Lateral

- Left-hand, right-hand or dual mounting on vertical profile (both inside and outside) at any height
- WIDTH adjustable (165 to 265 mm)
- **Material / Finish**
  - Steel panel, anti-static, powder-coated structure.
- **Color**
  - RAL 9006 White aluminium
- **Loading capacity**
  - 250 N (static surface load)
- **Note**
  - The lowest mounting position corresponds to 80 mm (minimum ground clearance)
- **Supply schedule**
  - 1 computer support
  - Mounting material
- **How supplied**
  - Flat-packed kit

W	H	D	Order-no.	UP
			04.208.078.7	1 unit



CON20129

## Knürr Elicon® VC/VC-E Adapter Bracket for PC Mount

- Required in addition to computer mount 04.208.078.7 for front-side mounting!
- **Color**
  - RAL 9006 White aluminium

Model	Order-no.	UP
For front-side mounting	04.265.179.7	1 unit



CON20130



Suitable monitor mounting accessories can be found from page 179

**Dimensions in mm:** W = Width  
H = Height  
D = Depth  
h = Installation height  
d = Useful depth  
L = Length  
HU = Standard height unit, 1 HU = 44.45 mm  
19" = 482.6 mm, (ideal for 19" components in acc. with DIN 41494)  
UP = Unit of packaging  
kg = Weight  
**Conversion:** 1 inch = 25.4 mm  
1 pound = 453.6 g  
Replace 'x' with the number of your color choice